



Diamètre	Long. Tot.	Long. Utile	C.M. N° =
27,25	291	170	3
27,5	291	170	3
27,75	291	170	3
28	291	170	3
28,25	296	175	3
28,5	296	175	3
28,75	296	175	3
29	296	175	3
29,25	296	175	3
29,5	296	175	3
29,75	296	175	3
30	296	175	3
30,25	301	180	3
30,5	301	180	3
30,75	301	180	3
31	301	180	3
31,25	301	180	3
31,5	301	180	3
31,75	306	185	3
32	334	185	4
32,5	334	185	4
33	334	185	4
33,5	334	185	4
34	339	190	4
34,5	339	190	4
35	339	190	4
35,5	339	190	4
36	344	195	4
36,5	344	195	4
37	344	195	4
37,5	344	195	4
38	349	200	4
38,5	349	200	4
39	349	200	4
39,5	349	200	4
40	349	200	4
40,5	354	205	4
41	354	205	4
41,5	354	205	4
42	354	205	4
42,5	354	205	4
43	359	210	4
43,5	359	210	4
44	359	210	4
44,5	359	210	4
45	359	210	4

Diamètre	Long. Tot.	Long. Utile	C.M. N° =
45,5	364	215	4
46	364	215	4
46,5	364	215	4
47	364	215	4
47,5	364	215	4
48	369	220	4
48,5	369	220	4
49	369	220	4
49,5	369	220	4
50	369	220	4
50,5	374	225	4
51	412	225	5
51,5	412	225	5
52	412	225	5
52,5	412	225	5
53	412	225	5
53,5	417	230	5
54	417	230	5
54,5	417	230	5
55	417	230	5
55,5	417	230	5
56	417	230	5
56,5	422	235	5
57	422	235	5
57,5	422	235	5
58	422	235	5
58,5	422	235	5
59	422	235	5
59,5	422	235	5
60	422	235	5
61	427	240	5
62	427	240	5
63	427	240	5
64	432	245	5
65	432	245	5
66	432	245	5
67	432	245	5
68	437	250	5
69	437	250	5
70	437	250	5
75	442	255	5
80	514	260	6
85	519	265	6
90	524	260	6
95	529	275	6
100	534	280	6

DIN 345

Référence
980

Référence	980
Nuance	HSS
Type	Meulé/Fraisé
Aspect	Noir/Af. Blanc
Hélice	Normale
Goujure	Normale
Angle pointe	118°
Affûtage	Standard
Utilisation	F A Ad lx Al

