


TARAUD MACHINE HSS ISO 529 GUN



APPLICATION

Pour application générale :
Acier non allié jusqu'à 80 kg
Acier faiblement allié < 90 kg
Fonte FT , FGS

For general use :
Steel up to app. 800 N/mm²
Low alloyed steel < 900 N/mm²
Cast iron , malleable cast iron

Diamètre	Pas mm	Diam. Foret	Long. Totale	Diam. Queue	Carré
M2	0.4	1,6	41	2,5	2
M2.5	0.45	2,05	44,5	2.8	2,24
M3	0.5	2,5	48	3,15	2,5
M4	0.70	3,3	53	4	3,15
M5	0.80	4,2	58	5	4
M6	1.00	5	66	6,3	5
M8	1.25	6,75	72	8	6,3
M10	1.50	8,5	80	10	8
M12	1.75	10,25	89	9	7,1
M14	2.00	12	95	11,2	9
M16	2.00	14	102	12,5	10
M18	2.50	15,5	112	14	11,2
M20	2.50	17,5	112	14	11,2
M22	2,50	19,5	118	16	12,5
M24	3,00	21	130	18	14
M27	3,00	24	135	20	16
M30	3,50	26,5	138	20	16


COFFRET DE 7 TARAUDS MACHINE M3 À M12



ISO 529

Référence
BB205

Référence	BB205
Classe de tolérance	ISO 6 H
Nuance	HSS
Coupe à	Droite
Goujures	Droites
Entrée forme	B/Gun



Utilisation

F	A	Ad	Ix	Al
●	●	●	●	●



Référence
A205/M312